

# GPS3602

## Internal Passive GPS Antenna

### Features

- ◆ Passive GPS antenna
- ◆ Fed by micro-coax/connector
- ◆ Compact Dimensions
- ◆ Ideal for portable devices

### Specifications

Radiating element	Patch (passive)
Frequency range	1575.42 MHz
Gain @ Zenith	1.5 dB typical
VSWR	<2:1 @ Centre Frequency
Bandwidth	8 MHz Typical
Polarisation	RHCP
Output Impedance	50 Ohm
Cable / Connector	100mm microcoax, IPEX (U.FL) connector
LNA	None
Dimensions	20 x 20 x 6mm

### Popular Ordering Options

FGPS35239-IPX-10	GPS3602 passive patch antenna with 100mm cable and IPEX connector
------------------	---

Specifications subject to change without notice.

5 Little Balmer  
Buckingham Industrial Park  
Buckingham  
MK18 1TF  
UK

Tel: +44 (0)1280 824055  
Fax: +44 (0)1280 817179  
Email: [sales@ead-ltd.com](mailto:sales@ead-ltd.com)  
Web: [www.ead-ltd.com](http://www.ead-ltd.com)

**EAD**   
embedded antenna design ltd  
*Delivering Antenna Innovation*